


H570S6 VER:0.1 Specification



H570S6 VER:0.1 Front View



H570S6 VER:0.1 IO View



H570S6 VER:0.1 Lateral View

Model No.	H570S6 VER:0.1
Processor	Support LGA1200 10 th /11 th Intel® Celeron/Pentium/Core™ i3/i5/i7/i9 processor Note: support 10 th /11 th Gen 125W CPU
Chipset	Intel® Q570 chipset
Memory	2* DDR4 SODIMM RAM slot, 3200MHz, up to 128GB
Display	Integrated Intel®HD Graphics, support DirectX12.1,OpenGL4.5, 4K display 1* DP port, support resolution up to 1920X1200@60Hz 1* HDMI1.4, support resolution up to 4096x2304 @24Hz
LAN	2* Intel ®I226V Gigabit LAN port, support Wake On LAN / PXE function
Storage	6* SATA3.0 hard disk port, transfer speed up to 6Gbps (Q570 chipset support at most 6*SATA, SATA7/8 no work) 2* M.2 slot, support M.2 2280 NVME PCIE X4 SSD
Audio	Onboard ALC897 7.1+2 channel high fidelity audio controller, support MIC/Line-out
Expansion Slot	1* PCIE3.0 X16 slot
Rear I/O Port	1* TF card slot 2* USB2.0 1* DP 1* HDMI 1* RJ45 RS232 serial port 2* USB3.0 2* RJ45 Gigabit LAN port 1* Line-out/MICK 2-in-1 audio port 1* clear CMOS button
Internal I/O Port	2* USB3.0, 2*10pin
Port	2* USB2.0, 2*5pin 1* Front audio port, 2*5pin 1* Network LED indicator port, 1*4pin 1* Front panel function button and LED indicator port, 2*5pin 1* 8pin ATX power connector 1* 20pin ATX power connector
Fan Connector	1*4pin CPU fan connector, 2*4pin system fan connector
GPIO	Support 4-in 4-out GPIO
BIOS	128Mb Flash ROM



Watchdog Support hardware reset function (L256, 0~255 seconds)
OS Support Windows 10/Windows 11/Linux
Power Type Adopt ATX 20Pin and 8pin power supply
Working Temp. 0°C~60°C
Storage Temp. -20°C~70°C
Working Humidity 5%-95% relative humidity, non-condensing
Dimension 170mm x 170mm

Order Information:

No.	Model	Processor	Frequency	Southbridge	Memory	VGA	HDMI	DP	LAN	USB	COM	RS485/422	Power
1	H570S6 VER:0.1	LGA1200	/	Q570	2*DDR4	/	1	1	2*I226V	8	1	/	ATX